

NYS208

Right Angle, stereo 3 pole



Article Variations

| Article Name | Details | Packaging |
|--------------|---|-----------|
| NYS208 | silvery handle, black plastic cover and bushing | |

Technical Information

Product

| | |
|------------------------|--------|
| Title | NYS208 |
| Connection Type | Plug |

Electrical

| | |
|------------------------------|---|
| Contact Resistance | $\leq 10\text{m}\Omega$ |
| Insulation Resistance | $\geq 200\text{ M}\Omega(\text{Initial})$ |
| Dielectric Strength | 0.5 KVdc 50HZ |

Mechanical

| | |
|---------------------------------------|----------------------|
| Insertion and Withdrawal Force | $\leq 60\text{N}$ |
| Lifetime | >1,000 Mating Cycles |

| Material | |
|--------------------------|----------------|
| Inner | Steel |
| Tip | Brass |
| Bushing | PA66+30%GF |
| Insulation | PVC |
| Front Shell | Zinc |
| Insulation | PA66+30%GF |
| Soldering Contact | Brass |
| Cover(Black) | PA6+30%GF |
| Bushing(Black) | POM |
| Inner | Brass |
| Bushing | PA66+30%GF |
| Sleeve | Brass |
| Insulation | PVC |
| Cable Clamp | Steel |
| Tip | Nickel Plating |
| Front Shell | Nickel Plating |
| Sleeve | Nickel Plating |
| Inner | Nickel Plating |
| Soldering Contact | Tin and Cer |
| Cable Clamp | Tin and Cer |